

SR PORTABLES



CLEO 3.6 AND CLEO X

OFF - GRID POWER STATION



4608WH

LITHIUM ION BATTERY

1-4

EXTENSIONS

IP54

WATER RESISTANCE

800W

DIRECT SOLAR INPUT

4000+

CYCLE LIFE

SMART PARALLEL BATTERY
UNIT



3600W

AC INVERTER

3072WH

BATTERY

7200W

SURGE OUTPUT

1500W

SOLAR INPUT

4000+

CYCLE LIFE



FC

C

E



Technical Specifications

| General parameters | CLEO 3.6 |
|--------------------|--|
| Battery Type | Lithium Iron Phosphate |
| Rated Capacity | 51.2V, 245Ah @12.5V/3072Wh (up to 80% at 4000 life |
| Net Weight | ≈46kg |
| Product Size | 563 mm*372 mm*423 mm |
| Operating Temp | 14 to 104°F (-10 to 40°C) |
| Charging Temp | 32 to 104°F (0 to 40°C) |
| Storage Temp | -4 to 113°F (-20 to 45°C) |

| Input | |
|------------------|----------------------------|
| AC Input Voltage | 200V-260V~7.5A, 50Hz |
| AC Input Power | AC 1800W |
| PV Input | DC 12V-150V~25A, 1500W Max |
| Car Charging | DC 12V/24V, 192W Max |
| Extra Battery | 1-4 extensions |

| Output | |
|---------------------------------|---|
| AC Output Voltage*5 | 240V~50Hz |
| Rated Output Power | 3600W |
| Parallel Connected AC Output | 7200W (only for units with parallel function) |
| Output Waveform | Pure Sine Wave |
| UPS Switching Time | 10ms |
| RV Output | 12V~30A |
| Cigarette Lighter Socket Output | 12V~10A |
| DC Output*2 | 12V~3A (Each) |
| USB-A Output*4 | 5V~3A, 9V~2A, 12V~1.5A, 18W Max |
| USB-C Output*2 | 5V/9V/12V/15V/20V~3A, 20V~5A, 100W Max |

| General parameters | CLEO X |
|--------------------|--|
| Battery Type | Lithium Iron Phosphate |
| Rated Capacity | 51.2V, 368Ah @12.5V/4608Wh (up to 80% at 4000 life cycles) |
| Net Weight | ≈49kg |
| Product Size | 563mm*372mm*423mm |
| Operating Temp | 14 to 104°F (-10 to 40°C) |
| Charging Temp | 32 to 104°F (0 to 40°C) |
| Storage Temp | -4 to 113°F (-20 to 45°C) |

| Input | |
|------------------------|--|
| CLEO 3.6 Input Power | 1800W (Charging via the CLEO 3.6 host) |
| CLEO 3.6 Extra Battery | 1-4 Extensions |
| CLEO-X PV Input | DC 12V-150V~25A, 800W Max |
| Car Charging | DC 12V/24V, 192W Max |

| Output | |
|---------------------------------|---------------------------------------|
| Cigarette Lighter Socket Output | 12V=10A |
| DC Output*2 | 12V=3A (Each) |
| USB-A Output | 5V=3A, 9V=2A, 12V=1.5A, 18W Max |
| USB-C Output | 5V/9V/12V/15V/20V=3A, 20V=3A, 60W Max |



Defense



Outdoors



Medical



Disaster Management



Off-grid Market



Agriculture



Maintenance



EV Charging



Financial Review
Most Innovative
Company



Good Design
Award Gold



59th Australian
Export and
Investment
Award



Governor of
Victoria Export
Award for
Sustainability



AFR BOSS
Best Place to
Work Award



Best Social
Impact
Innovation at
Finder Awards



Victorian
Exporter of
the Year
2023



Sustainability
and Green
Economy
Award 2023



SR Portables Pty. Ltd., is an Australian renewable energy solutions company. Our modern, efficient, and smart solar energy products are cost-effective, long-lasting & and environment-friendly with best-in-class technology. From commercial, and residential to off-grid applications, our products are designed to offer energy independence anytime, anywhere.

Visit our website www.srportables.com for more information or contact our technical team on +61 3 8618 6984