

## **ECO-FRIENDLY**

**SOLAR PANEL** 

HIGH

## WATERPROOF

**RUGGED DURABILITY** 

EASY





1

## **Technical Specifications**

| ITEMS                           | SPECIFICATIONS          |
|---------------------------------|-------------------------|
|                                 |                         |
| Maximum Power                   | 40.5W ± 5%              |
| Solar Cell Type                 | Monocrystalline         |
| Cell Efficiency                 | ≥19.5%                  |
| Maximum Operating Current (Imp) | > 2.2A ±5%              |
| Short Circuit Current           | > 2.45A ±5%             |
| Maximum Power Voltage (Vmpp)    | ≥18V                    |
| Open Circuit Voltage (Voc)      | 23.4V ±5%               |
| DC Output Connector             | DC5521 x1 or Other Type |
| IP Rating                       | IPX4                    |
| Working Temperature             | -30°C ~ 75°C            |
| Cloth Material                  | Camouflage PVC          |
| Expanded Size                   | 870x410x5mm             |
| Foldable Size                   | 410x350x45mm            |
| Net Weight                      | 2kg                     |



SR Portables Pty. Ltd., is an Australian renewable energy solutions company. Our modern, efficient, and smart solar energy products are cost-effective, long-lasting & and environment-friendly with best-in-class technology. From commercial, and residential to off-grid applications, our products are designed to offer energy independence anytime, anywhere.

Visit our website www.srportables.com for more information or contact our technical team on +61 3 8618 6984